

# 9500 Hot Farm

## 1. General Safety

- A. Must Follow General Safety rules Except where noted.
- B. Required Roll Cage or Factory Roll Protection Structure(ROPS)
- C. Required Ridged seat with lap belt required, High back and a 5 point harness is recommended. Required Helmet and Fire suit.

## 2. Chassis

- A. Tractors must have Hood and Grill, sheet metal to be stock length and location.
- B. Engine and Rear-end must be of the same brand/OEM combination. (Massy Ferguson & Perkins, Oliver & Cat/Waukesha and etc.)
- C. Front Axle
  - 1. Must have skid plates or ski's, unless using a factory front axle for make and model of tractor. Fabricated axle allowed.
  - 2. No Narrow Front axles**

## 3. Engine

- A. Must be OEM Block, 585 Cubic Inch Limit(Oliver2255 with Cat 3208 Allowed)
- B. Engine must bolt directly to clutch housing or with OEM adapter.
- C. Stock or OEM replacement 2 valve cylinder head. No overhead camshafts. OEM intake and exhaust required, no intake spacers.
- D. Any Injection Pump, with working governor.
- E. **All Turbos Need to be sealed and inspected by Fair Valley Performance for 2026.**
  - 1. S300SX-E 65mm with 2.58" inlet**
  - 2. S300SX-R 64mm with 2.56" inlet**
  - 3. HPT F2 6470 64mm with 2.57 inlet**
- F. 3000 RPM Limit. Must have a pig tail for sled monitor. Over RPM is DQ'd
- G. Dead Man Throttle not required.
- H. Diesel Fuel only, Water injection Allowed. (No Propane or NOS)
- I. No Inter-coolers allowed.

- 4. Tires Maximum 20.8x38 or equivalent square inch foot print. Agriculture tire with Top cut only.